

TS-709 SERIES





TS-709 B : 9P on-on

F : 9P (on)-on

C : 9P on-off-on

H : 9P (on)-off-on

G : 9P (on)-off-(on)



MODEL NO.	SWITCH FUNCTION			TERMINAL QUANTITY	CONNECTED TERMINALS		
	POS.1	POS.1	POS.1		POS.1	POS.1	POS.1
709-B	ON	NONE	ON	9P	1-2,4-S 7-g	—	2-3,5-6 8-g
709-F	(ON)	NONE	ON	9P	1-2,4-S 7-g	—	2-3,5-6 8-g
709-C	ON	OFF	ON	9P	1-2,4-S 7-g	—	2-3,5-6 8-g
709-H	MOM	OFF	ON	9P	1-2,4-S 7-g	—	2-3,5-6 8-g
709-G	MOM	OFF	MOM	9P	1-2,4-S 7-g	—	2-3,5-6 8-g

MOM=MOMENTARY

SPECIFICATION

1. RATING: 10A 250VAC, 15A 125VAC
15A 250VAC, 20A 125VAC
2. INSULATION RESISTANCE: DC 500V 200MΩ OR MORE
3. CONTACT RESISTANCE: DC 2-4V 1A 20MΩ OR LESS
4. WITHSTAND VOLTAGE: AC 1500V OR MORE

端子種類 Termination Options

H	S	U	T	P

專吉精密工業股份有限公司
TRANKEY MICRO-TECH CORP

產品 POWER TOGGLE SWITCH

PRODUCT

比例 1 : 1 單位 UNIT

SCALE

MM

公差

TOLERANCE

±0.3MM